

DECLARATION OF PERFORMANCE

Machine strength graded structural timber

1. Construction product

Machine strength graded structural timber which fulfills the requirements according to EN 14081-1:2005+A1:2011. For further or more detailed information on the delivered product, in addition to what is given below, see information on the packaging or in possible accompanying commercial document.

2. Type: 18101

M C16, Spruce (PCAB), Dimension: Thickness 32-75 mm, Width 75-225 mm

3. Intended use of the construction product

For load-bearing purposes in construction works designed according to Eurocode 5 (EN 1995) and for other uses where the strength and stiffness of the structure is essential.

4. Producer

Company: Stora Enso Eesti AS, Imavere Sawmill
Address: Kadastiku tee 1
72401 Imavere Järvamaa
Estonia
Telephone: +372 3849301
E-mail: alar.arula@storaenso.com
Web site: www.storaenso.com

6. System of assessment and verification of constancy of performance of the construction product

The Notified Body BM TRADA Latvija SIA (identification number 2358) has performed an initial inspection of the manufacturing plant and of the factory production control and performs continuous surveillance, assessment and evaluation of our factory production control. BM TRADA certification has issued EC Certificate of Factory Production Control no. 2358-CPR-039



storaenso

9. Declared performance

Performance for machine strength graded structural timber in conformity with the harmonized European standard EN 14081:2005+A1:2011 Timber structures – Strength graded structural timber with rectangular cross section – Part 1: General requirements.

Essential characteristics

Declared performance

Growth area

NNE Europe (Northern and North Eastern Europe)

Surface finish

Sawn or planed

Dry or wet graded

Dry graded

Grading machine

Dynagrade 1B

Strength properties	Characteristic values	
Bending strength	16 N/mm ²	EN 14081:2005+A1:2011
Compression parallel	17 N/mm ²	
Tension parallel	10 N/mm ²	
Resistance to shear	3,0 N/mm ²	
Mean modulus of elasticity parallel	7 kN/mm ²	
Durability	Class 4	
Reaction of fire	D-s2, d0	
Release of dangerous substances	No dangerous substances to be declared	

That the performance for our construction product machine strength graded structural timber is in accordance with the declared performance given above is certified:

Imavere 2016/03/31

Stora Enso Eesti As Imavere Sawmill



 (signature)

Mill Manager

