

BergaWrite 60

by Stora Enso



BergaWrite is a smooth uncoated woodfree paper for notebooks, diaries, pads etc offering ideal performance for ruling, folding and punching.

- Smooth surface
- Good whiteness
- High opacity

PRODUCER
Veitsiluoto Mill

TYPICAL END USES

Business to consumer
Business to business

PRINTING METHODS

Flexo
CSWO

TECHNICAL SPECIFICATIONS (target values)

Substance		g/m ²	60
Brightness	ISO 2470-2	%	105
CIE Whiteness	ISO 11475 (D65/10°)	%	150
Opacity	ISO 2471 (D65/10°)	%	84
Bulk	ISO 534	cm ³ /g	1.19
Roughness	Bendtsen TS	ml/min	170

REEL SPECIFICATIONS

Core: 152 mm
Width: min. 400 mm, max. 2500 mm
Diameters: 1200 mm, 1450 mm
Cores: 70* mm, 76* mm
Width: min. 400 mm, max. 2500 mm
Diameters: 1000 mm, 1200 mm

* full deckle required

CERTIFICATES

EU Ecolabel SE/011/01
Nordic Ecolabel 3044 0044
ISO 9001
ISO 14001
ISO 50001
OHSAS 18001
EMAS
FSC® CoC, license code FSC® C015932
PEFC™ CoC, licence code PEFC/02-31-86

ENVIRONMENT

Renewable fibre
Recyclable paper
Recyclable packaging materials

STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.