

EnviPress SC Paper Specification

Envipress stands for standard setting quality. Best Print results with high opacity.

End uses

Retail promotions	Catalogues
Newspaper inserts	Mail order
Mass circulation magazines	Supplements
TV guides	Gift-wrapping

EnviPress
悦印™

Product description

SC Prime super-calendered uncoated mechanical paper
(100% recycle)

Printing method

heatset web offset

Producer

Dawang Mill

Technical specification												
Item	Unit	Data										Test standard
Grammage	g/m ²	42	45	48	52	56	60	64	70	80	100	ISO 536
D65-Brightness	%	65	65	65	65	65	65	66	66	66	66	D65/10°
Y-value	%	64	64	64	64	65	65	65	65	65	65	ISO 2469,C/2°
Opacity	%	91	92	93	94	95	96	96	96	97	98	ISO 2471
Gloss Hunter	%	32	32	32	32	32	32	32	32	32	32	ISO 8254-1
Roughness PPS 1MPa	µm	1.65	1.65	1.65	1.65	1.65	1.65	1.65	1.65	1.65	1.65	ISO 8791-4
Bulk	cm ³ /g	1.0	1.0	1.0	1.0	1.0	1.0	0.95	0.95	0.95	0.95	ISO 534
Thickness	µm	42	45	48	52	54	57	61	67	76	95	ISO 534

Reel specifications

Trimmed width	679 cm
Core	76 mm
Max. Width	320 cm
Min. Width	50 cm
Max. Diameter	150 cm
Min. Diameter	80 cm
Max. Weight	3500 kg

Wrapping

Polyethylene laminated
Kraft paper

Environment

Renewable fibre
Recyclable paper
Recyclable packaging materials

FSC® C015932



ISO 14001:2004



Certificate No.:
8827-2010-AE-FIN-FINAS

ISO 9001:2008



Certificate No.:
88215-2010-AQ-FIN-FINAS

OHSAS 18001:2007



Certificate No.:
88218-2010-AHSD-FIN-FINAS



中国环境标志(II)型认证