

Exo 68, 72, 76, 80

by Stora Enso



Exo is a machine finished uncoated mechanical newsprint speciality.

- First class printability and runnability
- Overall cost efficiency

PRODUCER

Anjala Mill

TYPICAL END USES

Inserts
Supplements
Advertisements
Magazines
Special Newspapers
Free sheets

COLOUR PROFILE

FOGRA 42

PRINTING METHODS

CSWO
Digital

TECHNICAL SPECIFICATIONS (target values)

Substance		g/m ²	45	49	52	55	60	65	70
Bulk	ISO 534	cm ³ /g	1.6	1.6	1.6	1.6	1.6	1.6	1.6
Thickness	ISO 534	µm	72	78	83	88	96	104	112
Brightness	ISO 2470-2 (D65/10°)	%	68-72	68-72-76-80	68-72-76-80	68-72-76-80	68-72-76-80	76-80	76
Opacity	ISO 2471	%	89-90	89-92-93	92-93	92-93	94-95	95	96

REEL SPECIFICATIONS

Core: 76 mm
Trimmed width: 8550 mm
Width: min. 300 mm, max. 3000 mm
Diameters: min. 1000, max. 1500 mm
Max. weight: 5000 kg

CERTIFICATES

The EU Ecolabel FI/011/007
ISO 9001
ISO 14001
ISO 50001
OHSAS 18001
FSC® CoC, license code FSC® C015932
PEFC™ CoC, licence code PEFC/02-31-86

ENVIRONMENT

Renewable fibre
Recyclable paper
Recyclable packaging materials

STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.