

Flyo

by Stora Enso



Flyo is a smooth machine finished uncoated mechanical paper. It is based on 100% recycled fibre.

- Good image reproduction
- Brilliance of colours due to better ink hold out property
- Good printability for short shelf life products

PRODUCER
Sachsen Mill

TYPICAL END USES

Commercial flyers
Supplements

FINISH

Gloss

PRINTING METHODS

HSWO

COLOUR PROFILE

HSWO:
PSO_SNP_paper_eci.icc
Rotogravure:
PSRgravureMF.icc

L* a* b* values	L*	a*	b*	Fluorescence (ISO 12647-2)
Flyo (D50/C2°)	83	-0.3	4.5	Faint

TECHNICAL SPECIFICATIONS (target values)

Substance		g/m ²	40	45	48.8
Brightness	ISO 2470 C/2°	%	58.5	58.5	58.5
Opacity	ISO 2471 (D65/10°)	%	91	93	94
Smoothness BENDTSEN	ISO 8791-2	%	80	80	80
Bulk	ISO 534	cm ³ /g	1.3	1.3	1.2
Thickness	ISO 534	µm	51	57	60

REEL SPECIFICATIONS

Cores: 76 mm & 150 mm
Trimmed width: 9150 mm
Width: min. 300 mm, max. 3100 mm
Diameters: 1250 mm (& 1500 mm)
Max. weight: 4000 kg

ENVIRONMENT

100% recovered fibre content
Renewable fibre
Recyclable paper
Recyclable packaging materials

CERTIFICATES

The EU Ecolabel FI/11/002
Blue Angel UZ
ISO 9001
ISO 14001
ISO 50001
OHSAS 18001
EMAS
FSC® CoC, license code FSC® C015932
PEFC™ CoC, licence code PEFC/02-31-86

STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.