

Novobase

by Stora Enso



Novobase is a single layer mechanical wallpaper base in the grammage range 90 g/m².

PRODUCER
Anjala Mill

TYPICAL END USES
Wall coverings

CONVERTING METHODS
All PVC coating methods

TECHNICAL SPECIFICATIONS (target values)

Substance		g/m ²	90
Bulk		cm ³ /g	1.8
Thickness	ISO 534	µm	162
Brightness	ISO 2470-2 (D65/10°)	%	64
Cobb 60	ISO 535	g/m ²	17
Wet expansion cd	Mod. ISO 5635	%	1.5

REEL SPECIFICATIONS

Core: 71 mm, 76 mm
Trimmed width: 5400 mm
Width: min. 300 mm, max. 2500 mm
Diameters: min. 1000 mm, max. 1250 mm
Max. weight: 3000 kg

CERTIFICATES

ISO 9001
ISO 14001
ISO 50001
OHSAS 18001
FSC® CoC, license code FSC® C015932 *
PEFC™ CoC, licence code PEFC/02-31-86 *
(* FSC or PEFC paper is only delivered on customer request.)

ENVIRONMENT

Renewable fibre
Recyclable paper
Recyclable packaging materials

STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.