

# Novobase

by Stora Enso



Novobase is a single layer mechanical wallpaper base in the grammage range 90 g/m<sup>2</sup>.

**PRODUCER**  
Anjala Mill

## TYPICAL END USES

Wall coverings

## CONVERTING METHODS

All PVC coating methods

## TECHNICAL SPECIFICATIONS (target values)

Substance		g/m <sup>2</sup>	90
Bulk		cm <sup>3</sup> /g	1.8
Thickness	ISO 534	µm	162
Brightness	ISO 2470-2 (D65/10°)	%	64
Cobb 60	ISO 535	g/m <sup>2</sup>	17
Wet expansion cd	Mod. ISO 5635	%	1.5

## REEL SPECIFICATIONS

Core: 71 mm, 76 mm  
Trimmed width: 5400 mm  
Width: min. 300 mm, max. 2500 mm  
Diameters: 1000 mm, 1200 mm, 1250 mm  
Weight: max. 3000 kg

## ENVIRONMENT

Renewable fibre  
Recyclable paper  
Recyclable packaging materials

## STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.